

This Information Is Provided By
CBTricks.com

How to install the Powerband RFX75
on Cobra 148 (early models) series radios.

Liability of damages to any equipment is the sole responsibility of the user!
Downloading, viewing, or using any information provided on these pages
automatically accepts the user to the terms of this agreement!
Modifications are provided for information purposes only!
Supporters of CBTricks.com paid for the hosting so you would have this file.

CBTricks.com is a non-commercial personal website was created to help promote the exchange of service, modification, technically oriented information, and historical information aimed at the Citizens Band, GMRS (CB "A" Band), MURS, Amateur Radios and RF Amps.

CBTricks.com is not sponsored by or connected to any Retailer, Radio, Antenna Manufacturer or Amp Manufacturer, or affiliated with any site links shown in the links database. The use of product or company names on my web site is not endorsement of that product or company.

The site is supported with donations from users, friends and selling of the Site Supporters DVD's to cover some of the costs of having this website on the Internet instead of relying on banner ads, pop-up ads, commercial links, etc. Thus I do not accept advertising banners or pop-up/pop-under advertising or other marketing/sales links or gimmicks on my website.

All the money from donations is used for CBTricks.com I didn't do all the work to make money (I have a day job). This work was not done for someone else to make money also, for example the eBay CB sellers.

All Trademarks, Logos, and Brand Names are the property of their respective owners.
This information is not provided by, or affiliated in any way with any radio or antenna Manufacturers.

Thank you for any support you can give.

For information on how to Support CBTricks.com
<http://www.cbtricks.com/support/>

The user is solely responsible for making sure that any modifications made to the radio unit must meet all Federal and State Regulations or the Country of use! Liability of damages to any equipment is the sole responsibility of the user! Downloading, viewing, or using any information provided on these pages automatically accepts the user to the terms of this agreement! Modifications are provided for information purposes only! Disclaimer: CBTricks.com does not warrant the accuracy of the information contained herein nor is it responsible for any errors or omissions and assumes no liability for the content on this site. While CBTricks.com uses reasonable efforts to include accurate and up to date information, CBTricks.com makes no warranties or representations as to its accuracy or timeliness and assumes no liability or responsibility for any errors or omissions in the content of this site.


RFX75 - Cobra 148 Installation (Early Model 148 with 5 Pin Microphone Jack)

This is a preliminary installation sheet. SSB transmit audio is NOT perfect with this installation procedure. If you are only concerned with operation on AM, then this installation should be acceptable.

1. Remove D47, TR36 (final transistor), L35, L40, C31, C141, and C142 from the radio's PCB.
2. Change R183 to a 6.8 ohm resistor.
3. Drill holes and mount the RFX75 on the back of the radio per RFX75 instructions.
4. Solder the Red and Black wires to the back of the DC power jack (observe polarity!).
5. Solder the Yellow wire to the hole of D47 that is furthest from the external speaker jack (left hole on diagram below).
6. Solder the Orange wire to the hole of L39 that is closest to the front panel of the radio.
7. Solder the Blue wire to the hole of R180 that is closest to the front panel of the radio.
8. Solder the RF OUT coax center conductor to the right hole of L35 – this is the hole that is closest to the external speaker jack. Solder the coax shield to the chassis ground (C141 rear hole).
9. Solder the RF IN coax center conductor to the hole of L40 that is closest to the rear panel of the radio. Solder the coax shield to DC ground.
10. Solder the RX OUT coax center conductor to the hole of C31 that is closest to the front panel of the radio. Solder the coax shield to DC ground.
11. After double checking all connections re-tune the transmit and receive. Do not set carrier higher than 15 watts!
12. Some models may have a 4700pF ceramic disc capacitor soldered from the back of R185 to JP35 (this is near TR39 on the solder side of the board). This may need to be removed in order for the transmitter to function properly.
13. On some models you may need to add a 100ohm, 1/4 watt resistor from pin10 of IC5 (the transmit mixer) to ground to achieve maximum power.

The user is solely responsible for making sure that any modifications made to the radio unit must meet all Federal and State Regulations or the Country of use! Liability of damages to any equipment is the sole responsibility of the user! Downloading, viewing, or using any information provided on these pages automatically accepts the user to the terms of this agreement! Modifications are provided for information purposes only! Disclaimer: CBTricks.com does not warrant the accuracy of the information contained herein nor is it responsible for any errors or omissions and assumes no liability for the content on this site. While CBTricks.com uses reasonable efforts to include accurate and up to date information, CBTricks.com makes no warranties or representations as to its accuracy or timeliness and assumes no liability or responsibility for any errors or omissions in the content of this site.

R180 L40 L39 D47 C31 L35 C141 C142



The user is solely responsible for making sure that any modifications made to the radio unit must meet all Federal and State Regulations or the Country of use! Liability of damages to any equipment is the sole responsibility of the user! Downloading, viewing, or using any information provided on these pages automatically accepts the user to the terms of this agreement! Modifications are provided for information purposes only! Disclaimer: CBTricks.com does not warrant the accuracy of the information contained herein nor is it responsible for any errors or omissions and assumes no liability for the content on this site. While CBTricks.com uses reasonable efforts to include accurate and up to date information, CBTricks.com makes no warranties or representations as to its accuracy or timeliness and assumes no liability or responsibility for any errors or omissions in the content of this site.